## RADIO COMMUNICATIONS APPARATUS AND RADIO COMMUNICATION METHOD

Publication number:JP2008072733 (A)Also published as:Publication date:2008-03-27JP4247288 (B2)

Inventor(s): MURAKAMI YUTAKA; TAKABAYASHI SHINICHIRO; ORIHASHI

MASAYUKI; MATSUOKA AKIHIKO +
MATSUSHITA ELECTRIC IND CO LTD +

Applicant(s): Classification:

- international: H04J11/00; H04B1/707; H04B7/26; H04Q7/36; H04J11/00;

H04B1/707; H04B7/26; H04Q7/36


- European:

Application number: JP20070262556 20071005

Priority number(s): JP20010257027 20010827; JP20070262556 20071005

## Abstract of JP 2008072733 (A)

PROBLEM TO BE SOLVED: To provide a radio base station device and a radio communication method excellent in high-quality transmission and high-speed transmission.; SOLUTION: Orthogonal frequency division multiplex processing is performed on a transmission signal to form an OFDM modulation signal (daubed in FIG.) and orthogonal frequency division multiplex processing and code division multiple access processing are performed on a transmission signal to form an OFDM-CDMA modulation signal (shaded in FIG.) to transmit the OFDM modulation signal and the OFDM-CDMA modulation signal, which makes it possible to transmit data at a very high rate by using the OFDM modulation while making it possible to transmit data with a higher quality by using the OFDM-CDMA modulation than using the OFDM modulation, although it is slightly inferior to OFDM modulation in terms of high rate transmission.; COPYRIGHT: (C) 2008,JPO&INPIT



Data supplied from the espacenet database — Worldwide